

MINI RFID KEYPAD

Zipato Mini RFID Keypad combines RFID and Z-Wave protocol for access control purposes. You can identify yourself either by using numerical keypad or RFID key fob



DESCRIPTION

Zipato Mini RFID Keypad combines RFID and Z-Wave protocol for access control purposes. Users can identify themselves either by using manual code buttons on the numeric keypad, or by using a RFID key fob. The keypad fully supports Zipato automated security systems but also works with other Z-Wave enabled networks. "Home" and "Away" buttons allow arming and disarming of the security system or running any automation scenario. 1 RFID tag included, up to 20 codes supported.

PRODUCT FEATURES

- Arms or disarms security system
- User identification over numeric keypad or RFID key fobs (1 included)
- Can be used with any Z-Wave network/controller, regardless of the manufacturer
- Very low power consumption
- Low battery auto report
- Easy installation and relocation



TECHNICAL SPECIFICATION

PROTOCOL

- Z-Wave, RFID, Tag-it, ISO15693, ISO18000-3

POWER

- 2 x AA 1,5V batteries

OPERATING TEMPERATURE

- 10°C ~ 40°C

OPERATING HUMIDITY

- 30% to 80%

STORAGE TEMPERATURE

- -5°C ~ 65°C

STORAGE HUMIDITY

- 10% to 70%

RANGE

- Up to 30 meters line of sight (for indoor use only)

DIMENSIONS

- 17 x 62 x 62 mm

WEIGHT

- 45g

PACKAGE DIMENSIONS

- 122 x x 95 x 35 mm

PACKAGE WEIGHT

- 150g

FREQUENCY

- wt-rfid.au 921.42 MHz (AU)
- wt-rfid.eu 868.42 MHz (EU)
- wt-rfid.in 865.20 MHz (IN)
- wt-rfid.is 916.02 MHz (IS)
- wt-rfid.ru 869.02 MHz (RU)
- wt-rfid.us 908.42 MHz (USA/Canada)

REGULATION

- EMC 2004/108/EC, R&TTE 1995/5/EC, LVD 2006/95/EC, FCC Part 15

WARRANTY

- 1 year standard

NOTE: SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE