SMART COMBUSTIBLE GAS SENSOR

Used for detecting combusting gas leakage and preventing associated danger. It can also be used as Z-Wave repeater to extend wireless transmission distance.



## **TECHNICAL SPECIFICATION**

- → PROTOCOL
- Z-Wave
- **→ WORKING VOLTAGE**
- AC100~240V
- → AVARAGE CONSUMPTION
- <1.5 W
- **→ ALARM SOUND**
- 75dB (1m distance)
- **→ ALARM DENSITY**
- 6% LEL + 3% LEL (natural gas)
- **→ WIRELESS DISTANCE**
- <100m (open area)</p>
- → WORKING TEMPERATURE -10°C to 50°C (14°F to 122°F)
- → HUMIDITY
- <95%RH
- **→ PHYSICAL DIMENSION**
- Device: 68 mm x 75 mm x 76 mm

- Package: 84 mm x 72 mm x 87 mm
- → WEIGHT
- Device: 90 g
- Package: 128 g
- → REGULATORY COMPLIANCE
- Safety: UL
- EMC: FCC, CE
- RoHS
- **→ WARRANTY**
- 1 year standard

NOTE: SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE